


# M 20 - M 74 / E 70 - E 80 **Horizontal Coilformers**

The coilformers are made in gfr Polyamide PA66 of type p6g (RTI long-range temperature +125°C) and x2g5 (RTI long-range temperature +120°C). Pin material is tin bronze, tinned for solder-pins and brass, tinned for solder-tags. Max. solder temperature +350° C, 2 sec. Special materials - e.g. irradiated cross-linked – and designs on request, dimensions in mm/inch.



This group of horizontal coilformers is sorted by ferrite core / lamination size and each by pinning with straight pins, side-wrapping pins, solder-tags and conventional coilformers.

Most designs feature terminal strips with "noses" which provide tensionrelief of the winding wires and "stand-offs" which allow clean soldering of the coilformer onto the pcb to minimize cold-solder joints. Some coilformers also feature extended flanges to prevent clips sliding off.

# **Type**


Coilformer: M 55/1k/kk/p6g Coilformer: M 55/2k/kk/p6g


# Order-Code


01500-024 

### Accessories

Clip FK-E 55







# © 12/2011 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:

refer to Terms and Conditions of Sale

# **NORWE GmbH**

Postfach 13 56 51691 Bergneustadt Paulstraße 5, Pernze 51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0 Telefax +49 (0) 27 63-807-77 E-mail verkauf@norwe.de Internet www.norwe.de www.norwe.eu

# **NORWE Inc.**

P.O. Box 25 11

North Canton, OH 44720-0511

United States of America

Telefon +1-330 497-8113 Telefax +1-330 305-0592 E-mail usa@norwe.com Internet www.norwe.com