


#### M 20 - M 55 Vertical

The coilformers are made in gfr Polyamide PA66 of type p6g (RTI long-range temperature +125°C) and x2g5 (RTI long-range temperature +120°C). Pin material is tin bronze, tinned.

Pin material is tin bronze, tinned. Max. solder temperature +350° C, 2 sec.

Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/inch.




This group of vertical coilformers is sorted by ferrite core / lamination size and each by pinning with straight pins and side-wrapping pins. Most designs feature terminal strips with "noses" which provide tension-relief of the winding wires and "stand-offs" which allow clean soldering of the coilformer onto the pcb to minimize cold-solder joints. Some coilformers also feature extended flanges to prevent clips sliding off.


#### **Type**

Coilformer: M 55/1k/4-8/5.0-mq/p6g

Solder-pin: z811/ua

# 43.5 1.713 9, 26+ 0 23.7 0.933





### Order-Code


01660-024 73297-212

#### Accessories

on request

## Grid

View pin-side



#### © 01/2012 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:

refer to Terms and Conditions of Sale

#### **NORWE GmbH**

Postfach 13 56 51691 Bergneustadt Paulstraße 5, Pernze 51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0
Telefax +49 (0) 27 63-807-77
E-mail verkauf@norwe.de
Internet www.norwe.eu

#### NORWE Inc.

P.O. Box 25 11

North Canton, OH 44720-0511

United States of America

Telefon +1-330 497-8113
Telefax +1-330 305-0592
E-mail usa@norwe.com
Internet www.norwe.com