


### EE 8 - EE 32 Horizontal

The coilformers are made in gfr Polyamide PA66 of type p6g (RTI +125°C), x2g5 (RTI +120°C), A3X2G10, sw (RTI +115°C) and in gfr Polybutylene Terephthalate PBT of type pcg (RTI +130°C). Pin material: tin bronze, tinned and tag material: brass, tinned. Maximum solder temperature 350°C, 2 sec. Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/inch.



This group of horizontal coilformers is sorted by ferrite core / lamination size and each by pinning with straight pins, side-wrapping pins, solder-tags and conventional coilformers.

Most designs feature terminal strips with "noses" which provide tension-relief of the winding wires and "stand-offs" which allow clean soldering of the coilformer onto the pcb to minimize cold-solder joints. Some coilformers also feature extended flanges to prevent clips sliding off.

## **Type**

Coilformer: EE 12.6/1k/7-8/7.5-df/pcg Coilformer: EE 12.6/2k/7-8/7.5-df/pcg


Solder-pin: z808/ua


# Order-Code

09750-047 09751-047 73294-212

#### Accessories

Spring-Clip SB-EF 12.6





## **Grid** View pin-side



### © 12/2011 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:

refer to Terms and Conditions of Sale

### **NORWE GmbH**

Postfach 13 56 51691 Bergneustadt Paulstraße 5, Pernze 51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0
Telefax +49 (0) 27 63-807-77
E-mail verkauf@norwe.de
Internet www.norwe.eu

### NORWE Inc.

P.O. Box 25 11

North Canton, OH 44720-0511

United States of America

Telefon +1-330 497-8113
Telefax +1-330 305-0592
E-mail usa@norwe.com
Internet www.norwe.com