


SMD - Snap-on Caps

The Snap-on Caps are made in gfr Polyamide PA66 of type eg7 (RTI long-range temperature +120°C.)

Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/*inch*.




The spring-action Snap-on Cap allows quick assembly of the coilformers and the cores in their correct positioning. The caps have openings at the sides which allows additional glueing. They have a smooth top and can be used for pick-and-place.


When ordering please quote type and order-code.

Type I	Order-Code		A	B	C	I
EP 5/FG/eg7	93119-010		6.5 / 0.256	7.0 / 0.276	5.4 / 0.213	0.4 / 0.016
EP 7/FG/eg7	93112-010		8.6 / 0.339	10.4 / 0.409	9.0 / 0.354	0.5 / 0.020
EPX 7/FG/eg7	N0365-010	on request	8.6 / 0.339	10.4 / 0.409	11.3 / 0.445	0.5 / 0.020
EPX 9/FG/eg7	N0366-010	on request	10.6 / 0.417	10.4 / 0.409	11.3 / 0.445	0.5 / 0.020
EP 10/FG/eg7	93113-010		11.6 / 0.457	13.0 / 0.512	11.1 / 0.437	0.5 / 0.020
EPX 10/FG/eg7	N0367-010	on request	11.6 / 0.457	13.0 / 0.512	11.1 / 0.437	0.5 / 0.020
EP 13/FG/eg7	93114-010		14.2 / 0.559	14.0 / 0.551	12.0 / 0.472	0.5 / 0.020

Type II	Order-Code		A	B	C	I
EFD 10/FG/eg7	N0368-010	on request	11.7 / 0.461	12.1 / 0.476	5.7 / 0.224	0.5 / 0.020
EFD 12/FG/eg7	N0369-010	on request	13.7 / 0.539	14.0 / 0.551	6.6 / 0.260	0.5 / 0.020
EFD 15/FG/eg7	93166-010		16.4 / 0.646	17.2 / 0.677	8.1 / 0.319	0.5 / 0.020
EFD 20/FG/eg7	93167-010		21.6 / 0.850	22.2 / 0.874	9.9 / 0.390	0.5 / 0.020
EFD 25/FG/eg7	93168-010		26.6 / 1.047	27.0 / 1.063	13.0 / 0.512	0.5 / 0.020
EFD 30/FG/eg7	93169-010		31.8 / 1.252	32.4 / 1.256	13.1 / 0.516	0.6 / 0.024



Type I



Type II

© 10/2011 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:
refer to Terms and Conditions of Sale

NORWE GmbH

Postfach 13 56
51691 Bergneustadt

Paulstraße 5, Pernze
51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0

Telefax +49 (0) 27 63-807-77

E-mail verkauf@norwe.de

Internet www.norwe.de
www.norwe.eu

NORWE Inc.

P.O. Box 25 11
North Canton, OH 44720-0511
United States of America

Telefon +1-330 497-8113

Telefax +1-330 305-0592


E-mail usa@norwe.com

Internet www.norwe.com

SMD - Snap-on Caps

The Snap-on Caps are made in gfr Polyamide PA66 of type eg7 (RTI long-range temperature +120°C.)


Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/*inch*.



The spring-action Snap-on Cap allows quick assembly of the coilformers and the cores in their correct positioning. The caps have openings at the sides which allows additional glueing. They have a smooth top and can be used for pick-and place.

When ordering please quote type and order-code.

Type III	Order-Code		A	B	C	I
EE 5/FG/eg7	N0370-010	on request	6.4 / 0.252	6.3 / 0.248	3.6 / 0.142	0.4 / 0.016
EE 6.3/FG/eg7	N0371-010	on request	6.8 / 0.268	7.5 / 0.295	3.6 / 0.142	0.4 / 0.016
EE 8/FG/eg7	N0372-010	on request	9.1 / 0.358	9.1 / 0.358	4.5 / 0.177	0.4 / 0.016
EE 8.8/FG/eg7	N0373-010	on request	9.2 / 0.362	10.2 / 0.402	3.7 / 0.146	0.4 / 0.016
EE 10/FG/eg7	N0374-010	on request	11.2 / 0.441	11.4 / 0.449	5.5 / 0.217	0.5 / 0.020
EE 12.6/FG/eg7	N0375-010	on request	14.2 / 0.559	14.2 / 0.559	6.8 / 0.268	0.5 / 0.020
EE 16/FG/eg7	N0376-010	on request	17.6 / 0.693	17.8 / 0.701	8.5 / 0.335	0.5 / 0.020
EE 20/FG/eg7	N0377-010	on request	21.8 / 0.858	22.1 / 0.870	10.6 / 0.417	0.6 / 0.024



Type III

© 10/2011 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:
refer to Terms and Conditions of Sale

NORWE GmbH

Postfach 13 56
51691 Bergneustadt
Paulstraße 5, Pernze
51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0
Telefax +49 (0) 27 63-807-77
E-mail verkauf@norwe.de
Internet www.norwe.de
www.norwe.eu

NORWE Inc.

P.O. Box 25 11
North Canton, OH 44720-0511
United States of America

Telefon +1-330 497-8113
Telefax +1-330 305-0592
E-mail usa@norwe.com
Internet www.norwe.com