


EI, UI Coilformers

The coilformers are made in gfr Polyamide PA66 of type p6g (RTI long-range temperature +125 °C). Pin material is tin bronze, tinned and tag material is brass, tinned. Maximum solder temperature 350 °C, 2 sec. (Special materials and designs on request, dimensions in mm/inch).



Due to their designs with different connection systems (press-fit pins, bent over pins, soldertags, etc.) the coilformer-versions allow radial as well as axial binding on of the wires, matching your individual fields of application.

We are about to draw up a catalogue of this extensive series step by step – you will find the latest survey of available components on our homepage. For special designs and dimensions as well as available accessories please contact our technical specialists.

Type

Coilformer: EJ 30-10/1k/7-8/5.08-ii/p6g Coilformer: EJ 30-10/7-5k/7-8/5.08-ii/p6g

Solder-pin: h810/ua Solder-pin: z808/ua

22.8 1.8±0.3 0.888 0.071±0.012 12.8 0.504 7 0.276 0.197 14.5 0.571 10.5±0.2 0.413±0.008 11.5±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.413±0.2 0.


Order-Code

04380-024 04381-024 73496-212 73294-212

Accessories

on request

Grid View pin-side



© 07/2016 by NORWE GmbH

Warranties

refer to Terms and Conditions of Sale



Valid version of data sheet online

QR Online-Version

NORWE GmbH

Postfach 13 56 51691 Bergneustadt Paulstraße 5, Pernze 51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0
Telefax +49 (0) 27 63-807-77
E-mail verkauf@norwe.de
Internet www.norwe.eu

NORWE Inc.

P.O. Box 25 11 North Canton, OH 44720-0511 United States of America

Telefon +1-330 497-8113
Telefax +1-330 305-0592
E-mail usa@norwe.com
Internet www.norwe.com