


EI, UI Coilformers

The coilformers are made in Polyamide PA66 of type p6g (RTI long-range temperature +125°C). The material used is tin bronze, tinned (solder-pins) or brass, tinned (solder-tags).

Maximum solder temperature 350°C, 2 sec. (Special materials and designs on request, dimensions in mm/inch).



Due to their designs with different connection systems (press-fit pins, bent over pins, soldertags, etc.) the coilformer-versions allow radial as well as axial binding on of the wires, matching your individual fields of application.

We are about to draw up a catalogue of this extensive series step by step – you will find the latest survey of available components on our homepage. For special designs and dimensions as well as available accessories please contact our technical specialists.


Order-Code **Type** Accessories

Coilformer: 2UJ 48b/1k/2g2-/5.0-kv/p6g


Solder-tag: g2c/wc

09210-024 71070-259 on request


57 2.8±0.3



8.6



Grid View tag-side



© 07/2011 by NORWE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:

refer to Terms and Conditions of Sale

NORWE GmbH

Postfach 13 56 51691 Bergneustadt Paulstraße 5, Pernze 51702 Bergneustadt

Deutschland

Telefon +49 (0) 27 63-807-0 Telefax +49 (0) 27 63-807-77 E-mail verkauf@norwe.de Internet www.norwe.de www.norwe.eu

NORWE Inc.

P.O. Box 25 11

North Canton, OH 44720-0511

United States of America

Telefon +1-330 497-8113 Telefax +1-330 305-0592 E-mail usa@norwe.com Internet www.norwe.com