M 20 – M 74 / E 70 – E 80
Horizontal Coilformers

The coilformers are made in gfr Polyamide PA66 of type p6g (RTI long-range temperature +125° C) and A RV250 nat. (RTI long-range temperature +100° C).
Pin material is tin bronze, tinned for solder-pins and brass, tinned for solder-tags.
Max. solder temperature +350° C, 2 sec. Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/inch.



This group of horizontal coilformers is sorted by ferrite core / lamination size and each by pinning with straight pins, side-wrapping pins, solder-tags and conventional coilformers.
Most designs feature terminal strips with “noses” which provide tension-relief of the winding wires and “stand-offs” which allow clean soldering of the coilformer onto the pcb to minimize cold-solder joints. Some coilformers also feature extended flanges to prevent clips sliding off.

Type	Order-Code		Accessories
Coilformer: M 30a/1k/7-8/7.5-gj/A RV250 nat.	N0109-106	on request	Latching-Clip FB-E 30
Coilformer: M 30a/2k/7-8/7.5-gj/A RV250 nat.	N0110-106	on request	Spring-Clip SB-E 30
Solder-pin: z810/ua	73296-212		



Grid
View pin-side



01 A 0 K

© 07/2018 by NORWE ONE GmbH
Warranties:
refer to Terms and Conditions of Sale

Valid version of data sheet online

QR Online-Version

NORWE ONE GmbH
Paulstraße 5, Pernze
51702 Bergneustadt
Deutschland
Telefon +49 (0) 2763-807-0
WhatsApp +49 2763 807-0
E-mail verkauf@norwe.de
Internet www.norwe.de
www.norwe.eu

NORWE Inc.
P.O. Box 25 11
North Canton, OH 44720-0511
United States of America
Telefon +1-330 497-8113
E-mail usa@norwe.com
Internet www.norwe.com