


RM Power Conversion 45°, Specials


The coilformers are made in gfr Polyamide PA66 of type p6g (RTI long-range temperature +125° C).
Pin material: tin bronze, tinned.
Maximum solder temperature 350° C, 2 sec.
Special materials – eg. irradiated cross-linked – and designs on request, dimensions in mm/*inch*.




The pin layout on the lower flange of these specially designed coilformers allows simultaneous binding-on and winding of two wires (bi-filar).

Compared with standard RM-coilformers, 12–32 solder-pins are available. In addition, winding and soldering can be done fully automatic.

Type	Order-Code	Accessories
Coilformer: RM 8/1k/32-8/p6g	90034-024	
Solder-pin: z809/ua	73295-212	



Grid View pin-side



Stand 11/2011 | © 2026 NORWE ONE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:
refer to Terms and Conditions of Sale

Telefon +49 (0) 27 63-807-0
WhatsApp +49 2763 807-0
E-mail verkauf@norwe.de
Internet www.norwe.de
www.norwe.eu

NORWE ONE GmbH

51691 Bergeustadt
Paulstraße 5, Pernze
51702 Bergeustadt
Deutschland

NORWE Inc.

North Canton, OH 44720-0511
United States of America

Telefon +1-330 497-8113
E-mail usa@norwe.com
Internet www.norwe.com