


M 42 – M 102b

Coilformer elements


The components are made in grf Polyamide PA66 of type p6g (RTI long-range temperature +125°C). Pin material is tin bronze, tinned or brass, tinned for tags. Maximum solder temperature 350°C, 2 sec. Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/inch.




The coilformer elements are sorted according to size. The primary and secondary areas can be wound in separate working steps and the design also permits different connection systems.

The selection of components listed below and marked according to design A, B or C is essential to a complete coilformer.

Type	Order-Code	Component-Selection
Coilformer: M 42/x/2g2-/5.0-k/p6g Solder-tag: g2s/wd	03101-024 71040-261	A 1 x housing M 42/i 1 x frame M 42/r A 1 x housing M 42/t 1 x frame M 42/r



Grid View tag-side



Stand 07/2012 | © 2026 NORWE ONE GmbH

All dimensions in mm/inch

The permissible deviations according to DIN 16901 apply as tolerances

Warranties:
refer to Terms and Conditions of Sale



Telefon +49 (0) 27 63-807-0
 WhatsApp +49 2763 807-0
 E-mail verkauf@norwe.de
 Internet www.norwe.de
 www.norwe.eu

NORWE ONE GmbH

Postfach 13 56
 51691 Bergneustadt
 Paulstraße 5, Pernze
 51702 Bergneustadt
 Deutschland

NORWE Inc.

P.O. Box 25 11
 North Canton, OH 44720-0511
 United States of America

Telefon +1-330 497-8113
 E-mail usa@norwe.com
 Internet www.norwe.com