


Toroidal Core Potting Boxes (H-RG) for horizontal pcb mounting

The potting boxes are made in gfr Polyamide PA66 of type A RV250 nat. (RTI long-range temperature +100 °C). Pin material: tin bronze, tinned. Maximum solder temperature 350 °C, 2 sec. Special materials – e.g. irradiated cross-linked – and designs on request, dimensions in mm/*inch*.



Potting boxes for horizontal pcb mounting. The centre hole can be easily removed for applications requiring a feed-through. The design features "stand offs" to the pcb to eliminate cold soldering, or can be used as positioning aid.

Type

Box: H-RG 15.0/10.0-12.5/-8/A RV250 nat.
Solder-pin: z810/ua

Order-Code


66340-106
73296-212

Accessories

on request


wound toroidal core

diameter Ø 15.4/*Ø 0.606*
width 9.5/*0.374*



Grid

View pin-side



16 B 2 S

Stand 08/2018 | © 2026 NORWE ONE GmbH

Warranties:
refer to Terms and Conditions of Sale

NORWE ONE GmbH

Postfach 13 56
51691 Bergneustadt
Paulstraße 5, Pernze
51702 Bergneustadt
Deutschland

Telefon +49 (0) 27 63-807-0
WhatsApp +49 2763 807-0
E-mail verkauf@norwe.de
Internet www.norwe.de
www.norwe.eu

NORWE Inc.

P.O. Box 25 11
North Canton, OH 44720-0511
United States of America

Telefon +1-330 497-8113
E-mail usa@norwe.com
Internet www.norwe.com



Valid version of
data sheet online

QR Online-Version